


Dust and watertight connectors

UV resistant, waterproof, acrylic lens, can be aimed in any direction

Easily adjustable to direct the light where needed

Extruded aluminum with die cast mounting hardware

Use end caps (supplied) or interconnect multiple lights. Up to 16ft on one power supply.



AVAILABLE IN LENGTHS 2' to 8'.
LENGTHS CAN BE COMBINED TO FORM A CONTINUOUS RUN

LINEAR LIGHTING

DESCRIPTION

- Equivalent performance to T12 HO
- Can extend up to 2 feet from wall or as close as necessary for wall washing applications
- Easy to install
- LED's are maintenance free for at least 10 years (based on a 12 hour burn)
- Maintains brightness in cold weather

APPLICATION

Ideal for sign lighting, wall washing or general area lighting.

BENEFITS

HIGHLY EFFICIENT LED

The Adjustable linear LED uses fully tested high quality Phillips Rebel LEDs that produce a minimum of 1,100 lumens per foot.

Standard colour is a natural white 4300K, consult factory for other colour temperatures.

EXCELLENT LUMEN PERFORMANCE

Highly efficient heat sink maintains the junction temperature significantly below the recommended maximum ratings which allows the fixture to maintain 70% of initial lumens for at least 50,000 hours, well beyond the useful life of traditional fluorescent light sources.

CONTINUOUS RUN

Connect multiple fixtures in any combination for a continuous run in a large application.



TECH DATA

| PRODUCT | RD-L8-12 | RD-L8-14 | RD-L8-16 | RD-L8-18 |
|-------------------------------------|------------------------|------------------------|------------------------|------------------------|
| Length (one unit) | 2' | 4' | 6' | 8' |
| LED Power Consumption | 22.8W | 45.6W | 68.4W | 91.2W |
| Input Voltage | 120-277VAC | 120-277VAC | 120-277VAC | 120-277VAC |
| Colour Temperature | 4300K ¹ | 4300K ¹ | 4300K ¹ | 4300K ¹ |
| Light Output | Min 1,100 Lumens | Min 1,100 Lumens | Min 1,100 Lumens | Min 1,100 Lumens |
| Colour Rendering Index (CRI) | > 70 | > 70 | > 70 | > 70 |
| Lamp Life (L70) | > 50,000H ² | > 50,000H ² | > 50,000H ² | > 50,000H ² |
| Working Temperature | -30 to 50 °C | -30 to 50 °C | -30 to 50 °C | -30 to 50 °C |
| Ingress Protection Grade | IP65 | IP65 | IP65 | IP65 |
| Complies with CUL and CSA Standards | | | | |

¹ Natural white (4300k) standard. Other colours available, consult factory

² Approx. 10 years (with typical 12 hour daily usage)

ORDERING INFO example: RD-L8-14³

| SERIES | DESCRIPTION | LENGTH | WATTS | VOLTS | LED Colour | FINISH |
|--------|-----------------------|----------------------|----------------------------------|------------|------------------------------|---|
| RD-L8 | Adjustable Linear LED | 2' 4' 6' 8' | 22.8W 45.6W 68.4W 91.2W | 120-277VAC | NW Natural White 4300K | ■ AL Natural Aluminum Contact factory for other colour choices |

³ Consult factory for proper ordering code when a continuous run is required

*** Patent pending**

Contact us for more information: info@rdalighting.com

RDA Lighting Inc. 222 Islington Ave., Toronto, ON M8V 3W7
TEL. 416-252-9454 / 800-268-0381 | FAX. 416-252-9664 / 800-668-5517

