

The AWL2-LED80 is a wall pack with an adjustable head that can be aimed straight down for dark sky requirements or aimed out to deliver the light where required.



### APPLICATIONS

**Ideal for use on outdoor walls along perimeters of buildings, townhouses, condominiums, schools.**

<b>Project</b>	
<b>Type</b>	
<b>Date</b>	
<b>Notes</b>	

### SPECIFICATIONS

#### Construction

Die cast aluminum housing with tamperproof stainless steel hardware. Clear tempered glass lens with a gasket. There are 6 conduit entries. The unit has a unique hinge assembly for easy installation and a leveling bubble on the back box for proper alignment.

#### LED configuration

The AWL2-LED80 has two LED Chips On Board (COBs) that deliver 7 280 lumens. The LEDs have a color temperature of 5000K as standard. 3000K and 4000K also available. The LEDs have a CRI of greater than 70 and an operating temperature range of -40°C to +40°C.

#### Adjustable head

The fixture can be aimed 0° - 90° delivering more lumens on the ground where needed.

#### Electrical

Total system wattage of the unit is 77W. The standard unit has a high efficiency driver that operates at 120V - 277V.

#### Finish

Standard finish is Bronze. Please consult factory for custom color.




#### Accessories

Visor, Polycarbonate Lens, Wire Guard, Photocontrol, On/Off Sensor and 0 - 10V Dimmable Smart Sensor.

<b>Equivalent to</b>	<b>up to 250W MH</b>
<b>Input Watts</b>	<b>77W</b>
<b>Lumens</b>	<b>7 280 lumens</b>
<b>Efficiency</b>	<b>95 lumens per watt</b>

<b>Operating Temperature</b>	<b>-40°C to +40°C</b>
<b>Certification</b>	<b>cUL, DLC, IP65 meets LM79, LM80</b>
<b>LED life</b>	<b>100,000 hours</b>
<b>Colour Temperature</b>	<b>5000K (standard) 4000K, 3000K (option)</b>
<b>Warranty</b>	<b>5 Years</b>
<b>Total Harmonic Distortion</b>	<b>20%</b>
<b>Power Factor</b>	<b>0.9</b>

### DIMENSIONS



Shown with optional Motion Sensor





