

The 2HS is a fully adjustable twin head LED floodlight that can be rotated along both the vertical and horizontal axes to deliver light where needed.



### APPLICATIONS

The 2HS is ideal for outdoor use on parking garages, building perimeters and entrances.

<b>Project</b>	
<b>Type</b>	
<b>Date</b>	
<b>Notes</b>	

### SPECIFICATIONS

#### Construction

Durable aluminum construction making it suitable for outdoor use. Fixtures are rectangular in shape and have a clear tempered glass lens. The unit is fully adjustable to direct light where needed.

#### LED configuration

Each fixture head comprises one high efficiency LED Chip on Board. Complete fixture delivers a minimum of 2000 lumens. The LEDs have a color temperature of 5000K.

#### Electrical

Each fixture head has a power consumption of 14W making it a total of 28W (14W X 2).

#### Mounting

Fixture can be wall or ceiling mounted and mounts directly on to standard junction boxes.

#### Voltage

120V AC, 60 Hertz

#### Power factor

0.9

#### Finish

Available in black.

<b>Input Watts</b>	<b>28W (14W X 2)</b>
<b>Lumens</b>	<b>Min. 2000 lumens</b>
<b>Efficacy</b>	<b>71 lumens per watt</b>

<b>Operating Temperature</b>	<b>-40°C to +40°C</b>
<b>Warranty</b>	<b>5 Years</b>
<b>Color Temperature</b>	<b>5000K (standard)</b>
<b>LED Life(L70)</b>	<b>50,000 hours</b>

### DIMENSIONS

