

The P6RD LED bollard is an architectural bollard in a sleek design that provides uniform, glare free illumination.



### APPLICATIONS

**The P6RD bollard is an architectural bollard suitable for landscape and pathway lighting with glare free distribution. Ideal for use in townhouses, condominiums and parkettes.**

<b>Project</b>	
<b>Type</b>	
<b>Date</b>	
<b>Notes</b>	

### SPECIFICATIONS

#### Construction

Unit is a 6" round bollard with a dome shaped top. Body is made from extruded aluminum (.125 wall thickness) and fits over anchor base. It is secured with stainless steel set screws. Body has a powder coat finish. Upper body is a modular sealed unit to prevent moisture.

#### Optics

Reflector is a spun aluminum cone, anodized, type V distribution. Internal house shield is available as 90 or 180 degrees.

#### Lens

Clear acrylic lens. Frosted lens also available.

#### LEDS

Unit consists of 48 LEDs that deliver 1,040 lumens. Color temperature of LEDs is 5000K.

#### Electrical

Unit has high efficiency drivers that are 120 - 277 volts. System wattage is 15W.

#### Mounting

Spun steel base with three anchor bolts (1/2" x 12"). Lower body is secured to base with stainless steel set screws.

#### Finish

Standard powder coat finishes are Bronze, Black and White. Custom colors are available upon request.


#### Options

Frosted lens, 90 degree cutoff, 180 degree cutoff.

<b>Input Watts</b>	<b>15W</b>
<b>Lumens</b>	<b>1,040</b>
<b>Efficiency</b>	<b>70 lumens per watt</b>

<b>Operating Temperature</b>	<b>-40°C - +40°C</b>
<b>Warranty</b>	<b>5 Years</b>
<b>Color Temperature</b>	<b>5000K (standard)</b>
<b>LED life</b>	<b>100,000 hours</b>

### DIMENSIONS



ORDERING GUIDE

<b>P6RD</b>	-	<b>LED</b>	-		-		-		-	
				<b>COLOR TEMP.</b>		<b>VOLTAGE</b>		<b>FINISH</b>		<b>OPTIONS</b>
				5K - 5000K*		B - 120 - 277V*		BRZ - BRONZE* BLK - BLACK* WHT - WHITE* CC - CUSTOM COLOR		90 - 90 DEGREE CUTOFF 180 - 180 DEGREE CUTOFF CL - CLEAR LENS* FR - FROSTED LENS

\* Standard configuration