BLxS-LED

INSTALLATION INSTRUCTIONS





READ, UNDERSTAND, and **FOLLOW** these instructions before installing the equipment.

WARNING

Disconnect the Electrical supply power at the service panel (fuse or circuit breaker box). Failure to do so could result in serious injury or death. Only qualified electricians should install this fixture and the installation MUST conform to the Electrical Code and all local codes and ordinances. Ensure that only proper tools, materials, and equipment are used to complete the installation.


SAFETY

- Proper grounding is required to ensure personal safety.
- Fixture should be mounted in locations where unauthorized personnel will not readily subject it to tampering.
- Do not use this equipment for anything other than its intended purpose.
- Servicing this equipment should be performed by qualified service personnel.
- Save these instructions.
- This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the
 FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential
 installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in
 accordance with the instructions, may cause harmful interference to radio communications.
- Changes or modifications to this unit not expressly approved by the party responsible for compliance Could void the user authority to operate the equipment.
- MIN 90 °C SUPPLY CONDUCTOR

INSTALLATION


WALL MOUNT

- Use expansion bolts to secure the fixture on mounting surface.
- Keep enough length wires to ensure adjusting angle unhindered.
- Connect the wire in same color (correspond to wire N, L and G) together with a wire connector.



POLE MOUNT

- Connect the wire in same color (correspond to wire N, L and G) together with a wire connector.
- Put one end of the tube into the U-slot, and then fix the tube with two hex socket screws.
- Fixed -clamp on the pipe in a right position and make sure that the pipe will not rotate.
- Install the light fixture on the wall with four screws.



BLxS-LED







LUMEN SELECTABLE SWITCHES

The luminaire is designed with lumen selectable options, please follow the steps below:

- 1. Unscrew the knob cap before using the watt selectable function.
- 2. Toggle the DIP switch 1,2,3 as per the settings below.
- 3. Screw the power selectable cap back on. Ensure the cap is sealed properly.









WIRING

- Check that the line voltage is correct.
- Connect fixture **GROUND** (green) wire to power supply **GROUND** (green) wire.
- Connect fixture **WHITE** wire to power supply **NEUTRAL** wire.
- Connect fixture **BLACK** wire to power supply **LINE** wire.

