

INSTALLATION INSTRUCTIONS



ELECTRICAL SHOCK HAZARD

READ, UNDERSTAND, and FOLLOW these instructions before installing the equipment.

WARNING

Disconnect the Electrical supply power at the service panel (fuse or circuit breaker box). Failure to do so could result in serious injury or death. Only qualified electricians should install this fixture and the installation MUST conform to the Electrical Code and all local codes and ordinances. Ensure that only proper tools, materials, and equipment are used to complete the installation.

SAFETY

- Proper grounding is required to ensure personal safety.
- Fixture should be mounted in locations where unauthorized personnel will not readily subject it to tampering.
- Do not use this equipment for anything other than its intended purpose.
- Servicing this equipment should be performed by qualified service personnel.
- This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.
- Save these instructions.
- **MIN 90 °C SUPPLY CONDUCTOR**

INSTALLATION

1. Open the fixture by removing the four (4) screws located on the corners of the front housing.
2. Mount the fixture back plate to the J-Box (not provided) using the appropriate knock-out holes (Fig. 1), after installing provided gasket.
3. Make wiring connections, per below instructions, and make sure that all wires are safely contained inside.
4. **CCT & Lumen selectable switches:**
 - CCT and Power selectable switch is included in every luminaire.
 - Switches located inside housing compartment.
Fixture is set to highest wattage and 4000K standard.
5. Reinstall the front fixture housing, tighten the four corner screws.
6. After installing the fixture, apply silicone caulking around the top and both sides of the mounting plate and wall surface to ensure a weatherproof installation.
7. **Aiming:** Set vertical aiming by loosening (slightly) the screw on swivel arm. Aim fixture to desired illumination angle and securely re-tighten screw.




Fig. 1





Fig. 2

VEK-LED



INSTALLATION INSTRUCTIONS

WIRING

- Check that the line voltage is correct.
- Connect fixture **GROUND** (green) wire to power supply **GROUND** (green) wire.
- Connect fixture **WHITE** wire to power supply **NEUTRAL** wire.
- Connect fixture **BLACK** wire to power supply **LINE** wire
- The fixture includes 0-10V dimming functionality, connect **GREY** or **PINK** and **VIOLET** wires to a 0-10V dimming controller (optional).

